









SECTION B-B
SCALE 1:1



SECTION B-B
SCALE 1:1

NOTE:

- 1.MATERIAL SPECIFICATION:
1.HOUSING: HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.
2.CONTACTS: COPPER ALLOY
3.MID PLATE: STAINLESS STEEL
4.SHELL: STAINLESS STEEL
- 2.PLATING SPECIFICATION:
2-1.CONTACTS:
Ni 50u" MIN. UNDER PLATED OVER ALL.
Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.
(GOLD PLATING THICKNESS FOLLOW THE P/N)
GOLD FLASH PLATING ON SOLDER AREA
2-2.FRONT SHELL:
Ni 30u" MIN. UNDER PLATED OVER ALL.
- 3.MECHANICAL PERFORMANCE,
3-1.INSERTION FORCE: 0.5~2.0kgf.
3-2.REMOVAL FORCE: 0.8kgf~2.0kgf.
3-3.DURABILITY: 10000 CYCLES.
- 4.ELECTRICAL PERFORMANCE,
4-1. CURRENT RATING: 5A
VOLTAGE RATING: 20V
4-2.INSULATION RESISTANCE: 100MΩ MIN
4-3.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
4-4.LOW CONTACT RESISTANCE: INITIAL 40mΩ
AFTER 50mΩ
5. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -30°C~+80°C.
- 6.IR REFLOW:
THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 260°C.

Guangdong Tengjun Electronic Technology Co., Ltd

Website:

<https://www.tengjunconn.com>

TEL:

0769-23323869



PART NAME

USB TYPE C 16PIN,L-6.50mm
沉板1.60mm

PART NO.

TJDBC168622C016

TOLERANCE UNLESS OTHERWISE SPECIFIED:
X ±0.2
X.X ±0.15
X.XX ±0.10
X.XXX ±0.050

DRAWING:

Li

DATE:

2019.11.12

SCALE

SHEET

REV A0

CHECK:

Chen

DATE:

2019.11.12

1:1

1/3

SIZE: A4


APPROVAL:

Yuan



DATE:

2019.11.12

☐



RECOMMEND P.C.B LAYOUT (COMPONENT SIDE)
TOLERANCE FOR PCB LAYOUT IS ± 0.05



USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME
A1	GND
A4	VBUS
A5	CC1
A6	Dp1
A7	Dn1
A8	SBU1
A9	VBUS
A12	GND

PIN NUMBER	SIGNAL NAME
B12	GND
B9	VBUS
B8	SBU2
B7	Dn2
B6	Dp2
B5	CC2
B4	VBUS
B1	GND

Guangdong Tengjun Electronic Technology Co., Ltd

Website:

<https://www.tengjunconn.com>

TEL:

0769-23323869



PART NAME

USB TYPE C 16PIN, L-6.50mm
沉板1.60mm

PART NO.

TJDBC168622C016

TOLERANCE UNLESS OTHERWISE SPECIFIED:
X ± 0.2
X.X ± 0.15
X.XX ± 0.10
X.XXX ± 0.050

DRAWING:

Li

DATE:

2019.11.12

SCALE

SHEET

REV A0

CHECK:

Chen

DATE:

2019.11.12

1:1

2/3


SIZE: A4

APPROVAL:





Yuan

DATE:

2019.11.12



RoHS
Compliant




NOTES

1. 帶子引導長度

LEAD TAPE LENGTH

出料方向
PULL OUT DIRECTEON



2. 上帶 剝力為: 0.1~1.3N(10.2gf~130gf)

PEELING OFF FORCE OF TOP TAPE: 0.1~1.3N(10.2gf~130gf)

出貨運輸過程中一定注意:

THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT:

帶在運輸過程中不能數開

PEELING OFF SHOULD NOT BE ALLOWED DURING TRANSPORTATION

包明表 (The detail of the packing)						
品料 (Product No.)	包 容 量 (Packing Capacity)			重 量 Weight (Kg)		
	pcs/box	boxs/Carton	Pcs/Box	N.W./Pcs	N.W./Box	G.W./Box
TJDBC168622C016	1000	14	14000	----	----	----

Guangdong Tengjun Electronic Technology Co., Ltd

Website:

<https://www.tengjunconn.com>

TEL:

0769-23323869



PART NAME	USB TYPE C 16PIN,L-6.50mm 沉板1.60mm
PART NO.	TJDBC168622C016

TOLERANCE OTHERWISE SPECIFIED:	
X	±0.2
X.X	±0.15
X.XX	±0.10
X.XXX	±0.050

DRAWING:	Li	DATE:	2019.11.12	SCALE	SHEET	REV A0
CHECK:	Chen	DATE:	2019.11.12	1:1	3/3	SIZE: A4
APPROVAL:	Yuan	DATE:	2019.11.12			